


Formas y medidas / Shapes and sizes

Cuadrados / Square tiles



30x30x2,3cm
11,81"x11,81"x0,91"




25x25x2,2cm
9,84"x9,84"x0,91"



20x20x2,2cm
7,87"x7,87"x0,87"
*wall thick option 1,8 cm / 0,71"


Rodapiés / Skirting board

Canto redondeado
Beveled edge




20x10x1,8cm
7,87"x3,94"x0,71"

Canto redondeado
Beveled edge



25x10x2cm
9,84"x3,94"x0,79"

Tabica / Riser



28x14x2,2cm
11,02"x5,51"x0,87"

Rectángulo / Rectangular tile



15x15x1,8cm
5,91"x5,91"x0,71"



10x10x1,8cm
3,94"x3,94"x0,71"




7x7x1,8cm
2,76"x2,76"x0,71"




20x7x1,8cm
7,87"x2,76"x0,71"


Otras medidas / Special shapes



20x20x2,2cm
7,87"x7,87"x0,87"



20x23x1,6cm
7,87"x9,06"x0,63"



27,6x31,8x2,3cm
10,87"x12,52"x0,79"

Clasificación según normativa Europea / European standard classification

	STANDARD APPLIED	CLASSIFICATION
RESISTANCE TO THE SLIDE/ SLIPPAGE	UNE-ENV-12633:2003 (Rd)	CLASS 1: 15< Rd<= 35, on treated floors
	UNE-ENV-12633:2003 (Rd)	CLASS 3: Rd>45, on untreated floors
RESISTANCE TO FLEXION	UNE EN 1339:04	CLASS 3 (≤ 5,5 Mpa)
RESISTANCE TO ABRASION	UNE EN 1339:04	CLASS 3 (≤ 20 mm)

OBSERVATIONS

- In order to comply with European regulations, depending on the final treatment applied to the floor, classification of the cement tiles can vary.
- In order to obtain good results, enticdesigns recommends tiles should be treated, after being placed, and following their recommendations.